
	Value	Unit
	150	V
	3.3	V
	14	A
	51	mΩ

	Marking	MSL	Form	Reel(pcs)	Per Carton (pcs)
	SH1552P				

Electrical Characteristics (T_J = 25°C unless otherwise specified)

Symbol	Conditions	Min.	Typ.	Max.	Unit
Off Characteristics					
$V_{(BR)DSS}$		150	-	-	V
I_{DSS}		-	-	1.0	μ
I_{GSS}		-	-	±100	
$V_{GS(th)}$		2.3	3.3	4.3	V
$R_{DS(ON)}$		-	51	67	mΩ
R_g		-	1.1	-	Ω
C_{iss}		538	753	1016	pF
C_{oss}		55	77	104	pF
C_{rss}		-	12	-	pF
Q_g		-	11	17	nC
Q_{gs}		-	5	-	nC
Q_{gd}		-	2.4	-	nC
$t_{d(on)}$		-	8	-	ns
t_r		-	14	-	ns
$t_{d(off)}$		-	11	-	ns
t_f		-	2.8	-	ns
I_S		-	-		

Typical Performance Characteristics





Typical Performance Characteristics



Typical Performance Characteristics

Figure 11: Normalized Breakdown voltage vs. Junction Temperature





Test Circuit



Figure 1: Gate Charge Test Circuit & Waveform




Figure 2: Resistive Switching Test Circuit & Waveform




Figure 3: Unclamped Inductive Switching Test Circuit& Waveform






Figure 4: Diode Recovery Test Circuit & Waveform

All product information is copyrighted and subject to legal disclaimers.


Package Mechanical Data(PDFN3X3-8L)



NOTES:
1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M,1994.
2. ALL DIMNESIONS IN MILLIMETER (ANNGLE IN DEGREE).



Recommended Soldering Footprint



Information furnished in this document is believed to be accurate and reliable.
However, Jiangsu JieJie Microelectronics Co.,Ltd assumes no responsibility for the consequences of use without consideration for such information nor use beyond it.
Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Jiangsu JieJie complies with the agreement.
Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which may result from the use of such products and information.

is a registered trademark of Jiangsu JieJie Microelectronics Co.,Ltd.