Electrical Characteristics (T_J = 25°C unless otherwise specified)

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
Off Characteristics						
$V_{(BR)DSS}$	Drain-Source Breakdown Voltage	I_D = 250μA, V_{GS} = 0V	60	-	-	V
I_{DSS}	Zero Gate Voltage Drain Current	V_{DS} = 48V, V_{GS} = 0V	-	-	1.0	μ
I_{GSS}	Gate-Body Leakage Current	V_{DS} = 0V, V_{GS} = ±20V	-	-	±100	
On Characteristics						
$V_{GS(th)}$	Gate Threshold Voltage	V_{DS} = V_{GS}, I_D = 250μA	1.2	1.6	2.1	V
$R_{DS(ON)}$	Static Drain-Source ON-Resistance(4)	V_{GS} = 10V, I_D = 20A	-	11.3	14.7	mΩ
		V_{GS} = 4.5V, I_D = 15A	-	14.6	19.0	mΩ
Dynamic Characteristics						
R_g	Gate Resistance	f = 1MHz	-	1.8	-	Ω
C_{iss}	Input Capacitance	V_{GS} = 0V, V_{DS} = 30V, f = 1MHz	542	758	1024	pF
C_{oss}	Output Capacitance		275	385	520	pF
C_{rss}	Reverse Transfer Capacitance		19	26	35	pF
Q_g	Total Gate Charge	V_{GS} = 0 to 10V, V_{DS} = 30V, I_D = 20A	10	14	19	nC
Q_{gs}	Gate Source Charge		-	2.7	-	nC
Q_{gd}	Gate Drain("Miller") Charge		-	3.2	-	nC
Switching Characteristics						
$t_{d(on)}$	Turn-On DelayTime	V_{GS} = 10V, V_{DD} = 30V, I_D= 20A, R_{GEN} = 3Ω	-	5.4	-	ns
t_r	Turn-On Rise Time		-	14	-	ns
$t_{d(off)}$	Turn-Off DelayTime		-	16	-	ns
t_f	Turn-Off Fall Time		-	4.3	-	ns
Body Diode Characteristics						
I_S	Maximum Continuous Body Diode Forward Current		-	-	34	A
I_{SM}	Maximum Pulsed Body Diode Forward Current		-	-	135	A
V_{SD}	Body Diode Forward Voltage	V_{GS} = 0V, I_S = 20A	-		1.2	V
trr	Body Diode Reverse Recovery Time	I_F = 20A, di/dt = 100A/us	16	22	30	ns
Qrr	Body Diode Reverse Recovery Charge		-	11	-	nC

Notes: 1. Repetitive Rating: Pulse Width Limited by Maximum Junction Temperature.

2. E_{AS} condition: Starting T_J=25C, V_{DD}=30V, V_{GS}=10V, R_G=25ohm, L=3mH, I_{AS}=5.6A, V_{DD}=0V during time in avalanche.

3. R is measured with the device mounted on a 1inch^2 pad of 2oz copper FR4 PCB.

4. Pulse Test: Pulse Width ≤ ≤ 0.5%.

All product information is copyrighted and subject to legal disclaimers.

Typical Performance Characteristics

Figure 1: Power De-rating






Figure 2: Current De-rating



Typical Performance Characteristics

Figure 5: Output Characteristics





Typical Performance Characteristics

Figure 11: Normalized Breakdown voltage vs. Junction Temperature




Figure 12: Normalized on Resistance vs. Junction Temperature






Figure 14: $R_{DS(ON)}$ vs. V_{GS}





Figure 15: Maximum Safe Operating Area



Test Circuit



Figure 1: Gate Charge Test Circuit & Waveform




Figure 2: Resistive Switching Test Circuit & Waveform




Figure 3: Unclamped Inductive Switching Test Circuit& Waveform




Figure 4: Diode Recovery Test Circuit & Waveform

All product information is copyrighted and subject to legal disclaimers.

Package Mechanical Data(PDFN3X3-8L-D)

Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Microelectronics Co.,Ltd assumes no responsibility for the consequences of use without