DESCRIPTION:

The products are 10MBd high-speed opto-couplers in a plastic WSOP8 package. The device consists of a high efficient AlGaAs Light Emitting Diode and a high speed optical detector. This design provides excellent AC and DC isolation between the input and output sides of the optocoupler. The output of the optical detector features an open collector Schottky clamped transistor. The enable function allows the optical detector to be strobed. A guaranteed common mode transient immunity is up to 10kV/μs at 3.3V. The optocoupler operational parameters are guaranteed over the temperature range from -40 ~+110 . The products are widely used in isolation in line receivers, digital isolation for A/D, D/A conversion, ground loop elimination, feedback element in switching mode power supplier, pulse transformer replacement, power transistor isolation in motor drives, interface between microprocessor system, computer and their peripheral.

MAIN FEATURES

High isolation 7500 VRMS
High speed – 10MBd typical
Operating temperature range -40°C to 110°C
REACH & RoHS compliance
HBM: H3A; MM: M4; CDM: C3
CQC approved
VDE approved
UL approved

Truth Table

INPUT	OUTPUT
H	L
L	H

TEL

	Isolation Resistance	R_{ISO}	DC500V 40~60%R.H.	-	10^{12}	-	Ω
	Floating Capacitance	C_{IO}	V=0, f=1MHz	-	1	-	pF
Switching Characteristics	Trigger LED Current	I_{FT}	V_{CC}=5V V_O=V_{OL}	-	-	5	mA
	Propagation Delay Time to Logic Low	t_{PHL}	C_L=15pF, R_L=350Ω, I_F=7.5mA	-	-	60	ns
	Propagation Delay Time to Logic High	t_{PLH}		-	-	60	ns
	Pulse width distortion	$\|t_{PHL}-t_{PLH}\|$		-	-	35	ns
	Common Mode Transient Immunity at Logic High	CM_H	V_{CC}=3.3V, I_F=0mA, V_{CM}=1000V, R_L=350Ω	10	15	-	kV/μs
	Common Mode Transient Immunity at Logic Low	CM_L	V_{CC}=3.3V, I_F=10mA, V_{CM}=1000V, R_L=350Ω	10	15	-	kV/μs
	Rise Time	tr	C_L=15pF, R_L=350Ω, I_F=7.5mA	-	30	-	ns
	Fall Time	tf		-	30	-	ns


Recommended Operating Conditions

Operating Temperature	T_a	-40	-	85	
Supply Voltage	V_{CC}	2.7	-	3.6	V

VV


Output Pull-up Resistor	R_L	330	-	4k	Ω
Fan Out (at R_L=1kΩ per channel)	N	-	-	5	TTL Loads


ORDERING INFORMATION



Packing Quantity			
Option	**Quantity**	**Quantity – Inner box**	**Quantity –Outer box**
WSOP8	1200 Units/Reel	1 Reel/Inner box	5 Inner box/Outer box =6k Units

MARKING





Characteristics Curves

High Level Output Current vs. Ambient Temperature


High Level Output Current vs. Ambient Temperature

Package Dimension (Unit: mm)

Ref.	Dimensions					
	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	13.50		13.70	0.531		0.539
B	6.15		6.35	0.21	r }	0.250
C						
D	3.50		3.70			0.146
E	14.71		15.31			0.603
F	0.52			0.020		
G	16.36		16.86	0.664		0.664
H	0.10		0.40			0.016
I	3.65			0.144		
J			0.607	0.012		
K						


CARRIER TAPE SPECIFICATIONS (Dimensions in mm unless otherwise stated)

Option None



Ref.	Dimensions					
	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
D0	1.40	1.50	1.60	0.055	0.059	0.063
P0	3.90	4.00	4.10	0.154	0.157	0.161
P1	11.90	12.00	12.10	0.469	0.472	0.476
P2	1.90	2.00	2.10	0.075	0.079	0.083
E	1.65	1.75	1.85	0.065	0.069	0.073
F	11.40	11.50	11.60	0.449	0.453	0.457
T	0.35	0.40	0.45	0.014	0.016	0.018
W	23.70	24.00	24.30	0.933	0.945	0.957

REFLOW INFORMATION



Note:

1. Reflow soldering is recommended at the temperatures and times shown, no more than three times.

2. Avoid direct contact between the epoxy body and any tools or surfaces exceeding its maximum storage temperature.

3. Application of pressure on the epoxy body is prohibited at elevated temperatures. In specific scenarios, any applied force must not exceed 2.5N.

4. Ensure the component has cooled to ambient temperature before proceeding with any subsequent manufacturing steps.

5. The component has a shelf life of one year when stored under standard conditions.

6. Recommend storage Temp.: 0~40°C;

Recommend storage humidity: <60%;

MSL level: MSL 1

Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Microelectronics Co., Ltd. assumes no responsibility for the consequences of use without consideration for such information nor use beyond it. Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Jiangsu JieJie complies with the agreement.

Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which may result from the use of such products and information. This document supersedes and replaces all information previously supplied.

is a registered trademark of Jiangsu JieJie Microelectronics Co., Ltd.

Copyright © 2026 Jiangsu JieJie Microelectronics Co., Ltd. All rights reserved.