
## JCT620AH 20A SCR

Rev.A.1.1

With high ability to withstand the shock loading of large current, JCT620AH SCR provides high dV/dt rate with
It Tw 0.987 0 Td [0






J
CT
6
20
A
H
JieJie Microelectronics Co., Ltd.
SCRs
High junction temperature
A:TO-220A(InsTj 4o-Tj E/Spanhape
6:VDRM /VRRM 600V
IT(RMS):20A

FIG.7 Test circuit for inductive and resistive loads to IEC-61000-4-

| Order code | Voltage $V_{DRM}/V_{RRM}$ (V) | IGT(mA) | Package | Base qty. (pcs) | Delivery mode |
|---|---|---|---|---|---|
| JCT620AH | 600 | 15 | TO-220A(Ins) | 50 | Tube |



Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Microelectronics Co., Ltd. assumes no responsibility for the consequences of use without consideration for such information nor use beyond it. Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Jiangsu JieJie complies with the agreement. Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which may result from the use of such products and information. This document supersedes and replaces all information previously supplied.

is a registered trademark of Jiangsu JieJie Microelectronics Co., Ltd.

Copyright © 2025 Jiangsu JieJie Microelectronics Co., Ltd. All rights reserved.