
JCT625F 25A SCR

Rev.A.1.1

DESCRIPTION:

With high ability to withstand the shock loading of large current, JCT625F SCR provides high dV/dt rate with strong resistance to electromagnetic interference. It is especially recommended for use on solid state relay, motorcycle, power charger, T-tools etc. From all three terminals to external heatsink,JCT625F provides a rated insulation voltage of 2000 V_{RMS}, complying with UL standards (File ref: E252906). Package TO-220F is RoHS compliant.



MAIN FEATURES

Symbol	Value	Unit
$I_{T(RMS)}$	25	A
V_{DRM}/V_{RRM}	600	V
I_{GT}	≤20	mA

ABSOLUTE MAXIMUM RATINGS

Parameter	Symbol	Value	Unit
Storage junction temperature range	T_{stg}	-40-150	
Operating junction temperature range	T_j	-40-125	
Repetitive peak off-state voltage (T_j=25)	V_{DRM}	600	V
Repetitive peak reverse voltage (T_j=25)	V_{RRM}	600	V
Average on-state current (T_C ≤ 60)	$I_{T(AV)}$	16	A
RMS on-state current (T_C ≤ 60)	$I_{T(RMS)}$	25	A
Non repetitive surge peak on-state current (t_p=10ms, T_j=25)	I_{TSM}	320	A
Non repetitive surge peak on-state current (t_p=8.3ms, T_j=25)		352	
I^2t value for fusing (t_p=10ms , T_j=25)	I^2t	512	A^2s
Critical rate of rise of on-state current (I_G=2 × I_{GT}, f=100Hz , T_j=125)	dI/dt	200	A/μs

Peak gate current (t_p=20μs , T_j=125)	I_{GM}	5	A
Average gate power dissipation (T_j=125)	$P_{G(AV)}$	1	W
Peak gate power	P_{GM}	20	W
Peak pulse voltage (T_j=25 ; non-repetitive,off-state;FIG.7)	V_{pp}	0.5	kV

ELECTRICAL CHARACTERISTICS (T_j=25 unless otherwise specified)

Symbol	Test Condition	Value			Unit
		MIN.	TYP.	MAX.	
I_{GT}	V_D=12V R_L=33Ω	-	-	20	mA
V_{GT}		-	-	1	V
V_{GD}	V_D=V_{DRM} T_j=125 R_L=3.3kΩ	0.2	-	-	V
I_L	I_G=1.2I_{GT}	-	-	70	mA
I_H	I_T=500mA	-	-	60	mA
dV/dt	V_D=400V Gate Open T_j=125	1200	-	-	V/μs
t_{on}	I_G=20mA I_A=200mA I_R=20mA T_j=25	-	2	-	μs
t_{off}		-	50	-	


STATIC CHARACTERISTICS

Symbol	Parameter		Value(MAX.)	Unit
V_{TM}	I_{TM}=50A t_p=380μs	T_j=25	1.5	V
V_{TO}	Threshold voltage	T_j=125	0.72	V
R_D	Dynamic resistance	T_j=125	16	mΩ
I_{DRM}	V_D=V_{DRM} V_R=V_{RRM}	T_j=25	5	μA
I_{RRM}		T_j=125	0.5	mA


THERMAL RESISTANCES


Symbol	Parameter	Value	Unit
$R_{th(j-c)}$	junction to case(DC)	2.1	/W
$R_{th(j-a)}$	junction to ambient (DC)	62	/W

ORDERING INFORMATION



MARKING





ORDERING INFORMATION

Order code	Voltage V_{DRM}/V_{RRM} (V)	IGT(mA)	Package	Base qty. (pcs)	Delivery mode
JCT625F	600	20	TO-220F(Ins)	50	Tube

Document Revision History

Date	

PACKAGE MECHANICAL DATA



Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Microelectronics Co., Ltd. assumes no responsibility for the consequences of use without consideration for such information nor use beyond it. Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Jiangsu JieJie complies with the agreement. Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which may result from the use of such products and information. This document supersedes and replaces all information previously supplied.

is a registered trademark of Jiangsu JieJie Microelectronics Co., Ltd.

Copyright © 2025 Jiangsu JieJie Microelectronics Co., Ltd. All rights reserved.