
Peak gate current (t_p=20μs , T_j=125)	I_{GM}	10	A
Average gate power dissipation (T_j=125)	$P_{G(AV)}$	1	W
Peak gate power	P_{GM}	20	W
Peak pulse voltage (T_j			


J
CT
8
40
Z
JieJie Microelectronics Co., Ltd.
SCRs
8:VDRM /VRRM •800V
IT(RMS):40A
Z:TO-3P(Ins)



- & 7 =
; ; ; ; ; ;
Year
Month
Production
Code

FIG.1: Maximum power dissipation versus RMS on-state current





FIG.2: RMS on-state current versus case temperature

FIG.7 Test circuit for inductive and resistive loads to IEC-61000-4-5 standards.



Order code	Voltage V_{DRM}/V_{RRM} (V)	IGT(mA)	Package	Base qty. (pcs)	Delivery mode
JCT840Z	800	35	TO-3P(Ins)	30	Tube

Document Revision History

Date	Revision	Changes
Apr.13, 2023	A.1.0	Last update
Oct.16, 2025	A.1.1	Revise PACKAGE MECHANICAL DATA

Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Microelectronics Co., Ltd. assumes no responsibility for the consequences of use without consideration for such information nor use beyond it. Information mentioned in this document is subject to change without notice, apart mentioned from that when an agreement is sig //= χ M p ᵀ φ he um l· a p ɔ !