JST24A-600CW 25A TRIAC

Rev.A.1.1

The JST24A-600CW triac is suitable for general purpose AC switching. It can be used as an ON/OFF function in applications such as heating regulation, induction motor starting circuits, for phase control operation in light dimmers, motor speed controllers. JST24A-600CW snubberless triac is especially recommended for use on

i6o 484 Tw 24-27.9Td 57[(app2)6 (i)61.41D5 Td [(i6(ng)10 (462 A)5A)]9 M l24ii MA/TT28TwXP1


Average gate power dissipation (T_j=125)	$P_{G(AV)}$	0.5	W
Peak gate power	P_{GM}	10	W
Peak pulse voltage (T_j=25 ; non-repetitive,off-state;FIG.7)	V_{pp}	2.5	kV

(T_j=25 unless otherwise specified)

Symbol	Test Condition	Quadrant	Value		Unit
I_{GT}	V_D =12V R_L =33	- -	MAX.	35	mA
V_{GT}		- -	MAX.	1	V
V_{GD}	V_D =V_{DRM} T_j=125 R_L =3.3k	- -	MIN.	0.2	V
I_L	I_G=1.2I_{GT}	-	MAX.	70	mA
				80	
I_H	I_T =500mA		MAX.	50	mA
dV/dt	V_D=400V Gate Open T_j=125		MIN.	1500	V s
(dI/dt)c	j=125		MIN.	15	A/ms
t_{on}	I_G=40mA I_A=200mA I_R=20mA T_j=25		TYP.	7	s
t_{off}				50	

Symbol	Parameter	Value(MAX.)	Unit


FIG.7 Test circuit for inductive and resistive loads to IEC-61000-4-5 standards



Order code	Voltage V_{DRM}/V_{RRM}(V)	IGT(mA)	Package	Base qty. (pcs)	Delivery mode
		H I- J			
JST24A-600CW	600	35	TO-220A(Ins)	50	Tube

Document Revision History

Date	Revision	Changes
Apr.12, 2023	A.1.0	Last updated
Oct.13, 2025	A.1.1	Revise PACKAGE MECHANICAL DATA



Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Microelectronics Co., Ltd. assumes no responsibility for the consequences of use without consideration for such information nor use beyond it. Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Jiangsu JieJie complies with the agreement.

Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which may result from the use of such products and information. This document supersedes and replaces all information previously supplied.

is a registered trademark of Jiangsu JieJie Microelectronics Co., Ltd.

Copyright © 2025 Jiangsu JieJie Microelectronics Co., Ltd. All rights reserved.