
JST24A-800BW 25A TRIAC

Rev.A.1.1

DESCRIPTION:

The JST24A-800BW triac is suitable for general purpose AC switching. It can be used as an ON/OFF function in applications such as heating regulation, induction motor starting circuits, for phase control operation in light dimmers, motor speed controllers. JST24A-800BW snubberless triac is especially recommended for use on inductive loads. By using an internal ceramic pad, JST24A-800BW provides a rated insulation voltage of 2500 VRMS, complying with UL standards (File ref: E252906).Package TO-220A is RoHS compliant.



MAIN FEATURES

Symbol	Value	Unit
$I_{T(RMS)}$	25	A
V_{DRM} /V_{RRM}	800	V
I_{GT} / /	50/50/50	mA

ABSOLUTE MAXIMUM RATINGS

Parameter	Symbol	Value	Unit
Storage junction temperature range	T_{stg}	-40-150	
Operating junction temperature range	T_j	-40-125	
Repetitive peak off-state voltage (T_j=25)	V_{DRM}	800	V
Repetitive peak reverse voltage (T_j=25)	V_{RRM}	800	V
RMS on-state current (T_C 79)	$I_{T(RMS)}$	25	A
Non repetitive surge peak on-state current (full cycle , t_p=20ms , T_j=25)	I_{TSM}	250	A
Non repetitive surge peak on-state current (full cycle , t_p=16.6ms , T_j=25)		275	
I^2t value for fusing (t_p=10ms , T_j=25)	I^2t	340	A^2s
Critical rate of rise of on-state current (I_G=2× I_{GT} , f=100Hz , T_j=125)	dI/dt	100	A s
Peak gate current (t_p=20 s , T_j=125)	I_{GM}	4	A

JST24A

Average g





FIG.7 Test circuit for inductive and resistive loads to IEC-61000

ORDERING INFORMATION

PACKAGE MECHANICAL DATA



Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Microelectronics Co., Ltd. assumes no responsibility for the consequences of use without consideration for such information nor use beyond it. Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Jiangsu JieJie complies with the agreement.

Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which may result from the use of such products and information. This document supersedes and replaces all information previously supplied.

is a registered trademark of Jiangsu JieJie Microelectronics Co., Ltd.

Copyright © 2025 Jiangsu JieJie Microelectronics Co., Ltd. All rights reserved.