JST60CS-1200BW 60A TRIAC

Rev.A.1.1

The JST60CS-1200BW triac is suitable for general purpose AC switching. It can be used as an ON/OFF function in applications such as heating regulation, induction motor starting circuits, for phase control operation in light dimmers, motor speed controllers. JST60CS-1200BW snubberless triac is especially recommended for use on inductive loads. Package TO-247S is RoHS compliant.

Parameter	Symbol	Value	Unit
Storage junction temperature range	T_{stg}	-40-150	
Operating junction temperature range	T_j	-40-125	
Repetitive peak off-state voltage (T_j=25)	V_{DRM}	1200	V
Repetitive peak reverse voltage (T_j=25)	V_{RRM}	1200	V
RMS on-state current (T_C 92)	$I_{T(RMS)}$	60	A
[redacted]			

Peak pulse voltage (T_j=25 ; non-repetitive,off-state;FIG.7)	V_{pp}	1.1	kV

(T_j=25 unless otherwise specified)

Symbol	Test Condition	Quadrant	Value		Unit
I_{GT}	V_D =12V R_L =33	- -	MAX.	50	mA
V_{GT}		- -	MAX.	1.3	V
V_{GD}	V_D =V_{DRM} T_j=125 R_L =3.3k	- -	MIN.	0.2	V
I_L	I_G=1.2I_{GT}	-	MAX.	120	mA
				120	
I_H	I_T =1A		MAX.	80	mA
dV/dt	V_D=800V Gate Open T_j=125		MIN.	2000	V s
(dI/dt)c	j=125		MIN.	25	A/ms

t_{on} I_G=80mA I_A=400mA I_R=40mA
T_j=25

FIG.1: Maximum power dissipation versus RMS on-state current




FIG.2: RMS on-state current versus case temperature





FIG.7 Test circuit for inductive and resistive loads to IEC-61000-4-5 standards



Order code	Voltage V_{DRM}/V_{RRM}

Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Microelectronics Co., Ltd. assumes no responsibility for the consequences of use without consideration for such information nor use beyond it. Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Jiangsu JieJie complies with the agreement.

Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which may result from the use of such products and information. This document supersedes and replaces all information previously supplied.

is a registered trademark of Jiangsu JieJie Microelectronics Co., Ltd.

Copyright © 2025 Jiangsu JieJie Microelectronics Co., Ltd. All rights reserved.