T3050H-8E 30A TRIAC

Rev.A.1.0

DESCRIPTION:

The T3050H-8E triac is suitable for general purpose AC switching. It can be used as an ON/OFF function in applications such as heating regulation, induction motor starting circuits, for phase control operation in light dimmers, motor speed controllers. Compared to traditional triacs, T3050H-8E provides a very high switching capability up to junction temperatures of 150°C. Package TO-263 is RoHS compliant.

MAIN FEATURES

ABSOLUTE MAXIMUM RATINGS

Parameter	Symbol	Value	Unit
Storage junction temperature range	T_{stg}	-40-150	
Operating junction temperature range	T_j	-40-150	
Repetitive peak off-state voltage (T_j=25)	V_{DRM}	800	V
Repetitive peak reverse voltage (T_j=25)	V_{RRM}	800	V
RMS on-state current (T_C 0 117)	$I_{T(RMS)}$	30	A
Non repetitive surge peak on-state current (full cycle , t_p=20ms , T_j=25)	I_{TSM}	270	A
Non repetitive surge peak on-state current (full cycle , t_p=16.6ms , T_j=25)		297	

I^2t value for fus75.2 T Tf 12 0 0 12 231.e f 49f 4 T Tf 12 12 231.e f 49f 4 T Tf 12 0 231.e f 49f 4 T

Peak pulse voltage (T_j=25 ; non-repetitive,off-state;FIG.8)	V_{pp}	1.2	kV

ELECTRICAL CHARACTERISTICS (T_j=25 unless otherwise specified)

Symbol Test Cond kVI/75 3 Tw 10.0801 T 56.(4)15BMC53P1<0/MCID 105.4 759.2.0751 Tc 05248ae T 56

FIG.1 Maximum power dissipation versus RMS on-state current




FIG.2: RMS on-state current versus case temperature





FIG.3: RMS on-state current versus ambient temperature (printed circuit board FR4,copper

W K L F N Q H V V P I X O O F \ F O H

FIG.4: Surge peak on-state current versus number of cycles

FIG.7: Relative variations of gate trigger current, holding current and latching current versus junction temperature



ORDERING INFORMATION

Order code	Voltage V_{DRM}/V_{RRM} (V)	IGT(mA)	Package	Base qty. (pcs)	Delivery mode
		- -			
T3050H-8E	800	50	TO-263	50	Tube
T3050H-8E-TR263	T				

DELIVERY MODE



Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Microelectronics Co., Ltd. assumes no responsibility for the consequences of use without consideration for such information nor use beyond it. Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Jiangsu JieJie complies with the agreement.

Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which may result from the use of such products and information. This document supersedes and replaces all information previously supplied.

is a registered trademark of Jiangsu JieJie Microelectronics Co., Ltd.

Copyright © 2023 Jiangsu JieJie Microelectronics Co., Ltd. All rights reserved.